

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/052608 A1

(51) International Patent Classification⁷: **G01R 29/08**

(21) International Application Number:
PCT/KR2004/001509

(22) International Filing Date: 22 June 2004 (22.06.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0084207
25 November 2003 (25.11.2003) KR

(71) Applicant (for all designated States except US): ELEC-
TRONICS AND TELECOMMUNICATIONS RE-
SEARCH INSTITUTE [KR/KR]; 161, Gajeong-dong,
Yuseong-gu, Daejeon 305-350 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEE, Ae-Kyoung

[KR/KR]; #108-1103 Daelimdure Apt., Sinseong-dong,
Yuseong-gu, Daejeon 305-720 (KR). **CHOI, Hyung-Do**
[KR/KR]; 16-42, Dapsimni 4-dong, Dongdaemun-gu,
Seoul 130-800 (KR). **PACK, Jeong-Ki** [KR/KR]; 220,
Gung-dong, Yuseong-gu, Daejeon 305-355 (KR).


(74) Agent: SHINSUNG PATENT FIRM; 2F, Line Bldg.,
823-30 Yeoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METHOD FOR MEASURING ELECTROMAGNETIC RADIATION PATTERN AND GAIN OF RADIATOR USING
TEM WAVEGUIDE



(57) Abstract: A method for measuring electromagnetic radiation pattern and gain of radiator using TEM waveguide is disclosed. The method includes the steps of: a) measuring powers of output port of a transverse electric and magnetic (TEM) waveguide by changing arrangements of the radiator located within the TEM waveguide; and b) estimating a radiation power density of the radiator in free space, wherein the radiator is modeled as a dipole moment based on the powers of the output port of the TEM waveguide.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.